

A

Please refer to the V300 series hardware manual for more detailed information.

Electrical specifications					
Model	W	Rated power: W		Rated voltage	
V304E	2.4	2.4	DC24V	DC19.2~28.8V	DC24V, voltage range: DC19.2~28.8V
V307S	4.8	4.8			
V307E	4.8	4.8			
V310S	7.2	7.2			
V310E	7.2	7.2			
V315E	14.4	14.4			
V315E-4G	14.4	14.4			
V315E-WIFI	14.4	14.4			
V300-4G-ADP	—	—			Powered by HMI
V300-WIFI-ADP	—	—			

Environmental requirements				
	Item		Specifications	
	Altitude		≤2000m	
	Operating environment		≤2000m	
	Operating temperature		Installation within a control cabinet, open-type and indoor use	
	Storage temperature		-0~55℃	
	Ambient humidity		-0~55℃	
	Vibration resistance		-20~60	
	Pollution degree		-20~60	
	Cooling method		10~95%RH	
	IP rating		10~95%RH (non-condensation)	
	Enclosure material		5~150Hz X/Y/Z 1g/3.5mm	
			5~150Hz (X/Y/Z direction, 1g /3.5mm displacement)	
			Level 2	
			Natural air cooling	
			Front panel: IP65, Back housing: IP20	
			Self-extinguishable	

[illegible]

2 Removable terminal block mounting and dismounting

沿箭头方向插入端

CN

[illegible]



Indicator description



